


ENVIROGRAF® PRODUCT 25

INTUMESCENT PROTECTION SLEEVE SYSTEM FOR CABLES

All Electrical Products to comply with the revised 16th Edition of the IEE Regulations and Document B of UK Building Regulations



DESCRIPTION

A complete unit giving fire and smoke protection to electrical and plumbing services passing through fire barrier walls made from block, brick, concrete, and hollow plasterboard. The system comprises three parts:

- (A) A semi-flexible tube 200mm or 600mm long that can be cut to the right size to suit the floor or wall. In case of fire, this will intumesce, expands filling the hole, preventing spread of fire.
- (B) Two smoke protection units (one placed each side of the penetration) that allow the maintenance of services but, in a fire, prevent the spread of smoke. (See also Product 110).

USE

Fire barrier for use in walls and floors, where cables can be easily installed or removed.

PERFORMANCE

This product underwent a fire resistance test employing the general procedures and criteria of BS476 Part 22 (1987), achieving an integrity of 130 minutes in solid walls, and 67 minutes in hollow walls. Also tested at VNE to European Standard EN1363-1 (2000).

ORDERING REFERENCES :

Ref	Internal	External
ICP1	50mm	65mm
ICP2	90mm	115mm
ICP3	115mm	150mm
ICP4	165mm	210mm



Add suffix /2 for 200mm and /6 for 600mm. Other sizes are available