


# ENVIROGRAF® PRODUCT 43

## MAGNETIC TIMED DOOR HOLDER

(ACCEPTED BY FIRE BRIGADES AND BUILDING CONTROL OFFICERS)



### DESCRIPTION

An electro-magnetic timed door holder operating independently of an existing fire alarm system, with a master unit for mains voltage in and 24V out, with electro-magnet and armature plate. Units are available for single doors, double doors, or up to 4 doors.

### USE

Designed to hold open a single/double doors for up to 57 seconds, cutting down on draughts, noise, and loss of heat, as well as preventing buckling and distortion of doors, a common problem with permanent door holders. The 24V electro-magnet releases the door to be shut by the door closer as usual. Ideal for hospitals, residential homes, offices, computer suites, hotels, and warehouses. Can be supplied for operation by blind people. Holds the door open until the person has passed through the opened doorway. No wiring to existing fire alarm system as agreed by the fire brigade, because duration of door opening is under one minute.

### ORDERING REFERENCES:

<b>MHK1</b>	<b>Kit for one door</b>	<b>(1 control, 1 magnet, 1 plate)</b>
<b>MHK2</b>	<b>Kit for two doors</b>	<b>(1 control, 2 magnets, 2 plates)</b>
<b>MHK4</b>	<b>Kit for four doors</b>	<b>(1 control, 4 magnets, 4 plates)</b>
<b>MH24</b>	<b>24V magnet and armature (parts can be supplied separately)</b>	
<b>MH240</b>	<b>240V magnet and armature (parts can be supplied separately)</b>	
<b>SGC/2</b>	<b>Control unit only (if required separately)</b>	
<b>MDHB</b>	<b>Bracket for fixing magnetic door holder to wall</b>	

PATENTED